

Unique identification code of the product-type:	WIMOLASTIC (2020)
Intended use or uses:	All external installations and swimming pools beneath ceramic tiling.
Manufacturer:	WIM Sp. z o.o. ul. 18 Stycznia 28 97-300 Piotrków Trybunalski <a href="http://www.wim-chb.pl">www.wim-chb.pl</a>
System or systems of assessment and verification of constancy of performance:	System 3
Designated standard:	EN 14891:2012 EN 14891:2012/AC:2012 Approved body No. 1301 TECHNICKÝ A SKÚŠOBNÝ ÚSTAV STAVEBNÝ, n.o.

**Declared performance:**

Essential characteristics	Performance
Initial tensile adhesion strength.	≥ 0,5 N/mm <sup>2</sup>
Water tightness	no penetration
Crack bridging ability: <ul style="list-style-type: none"> <li>under standard conditions</li> </ul>	≥ 0,75 mm
Durability of initial tensile adhesion against climate / heat ageing action: <ul style="list-style-type: none"> <li>tensile adhesion strength after heat ageing</li> </ul>	≥ 0,5 N/mm <sup>2</sup>
Durability of initial tensile adhesion against water / humidity action: <ul style="list-style-type: none"> <li>tensile adhesion after water contact</li> </ul>	≥ 0,5 N/mm <sup>2</sup>
Durability of initial tensile adhesion against contact with lime water: <ul style="list-style-type: none"> <li>tensile adhesion after contact with lime water</li> </ul>	≥ 0,5 N/mm <sup>2</sup>
Durability of initial tensile adhesion after against freeze-thaw cycles: <ul style="list-style-type: none"> <li>tensile adhesion after freeze-thaw cycles</li> </ul>	≥ 0,5 N/mm <sup>2</sup>
Release of dangerous substances	NPD



The performance of the product is in conformity with the declared performance range.

This declaration of performance is issued in accordance to Regulation (EU) 305/2011 as it has effect in the United Kingdom under sole responsibility of the manufacturer listed above.

Signed for and on behalf of the manufacturer by Paweł Lisiński in Piotrków Tryb., on 11.04.2023

WIM Sp. z o.o.  
Wiceprezes Zarządu  
*Paweł Lisiński*  
Paweł Lisiński