

Unique identification code of the product-type:	WIM FLEX EXPRESS (2021)
Intended use or uses:	All internal and external tiling.
Manufacturer:	WIM Sp. z o.o. ul. 18 Stycznia 28 97-300 Piotrków Trybunalski tel.: +48 44 744 12 50 www.wim-chb.pl
System or systems of assessment and verification of constancy of performance:	System 3
Designated standard:	EN 12004:2007+A1:2012 Approved Body nr 0767 MPA Dresden GmbH Approved Body nr 2007 KIWA Bautest Dresden GmbH

Declared performance:

Essential characteristics	Performance
Reaction to fire	A1 A1 _{fl}
Bond strength expressed as: <ul style="list-style-type: none"> initial tensile adhesion strength early adhesion 	$\geq 1,0 \text{ N/mm}^2$ $\geq 0,5 \text{ N/mm}^2$
Durability of bond strength against climate/heat ageing action expressed as: <ul style="list-style-type: none"> tensile adhesion strength after heat ageing 	$\geq 1,0 \text{ N/mm}^2$
Durability of bond strength against water/humidity action expressed as: <ul style="list-style-type: none"> tensile adhesion strength after water immersion 	$\geq 1,0 \text{ N/mm}^2$
Durability of bond strength against freeze-thaw cycles expressed as: <ul style="list-style-type: none"> tensile adhesion strength after freeze-thaw cycles 	$\geq 1,0 \text{ N/mm}^2$
Release of dangerous substances	NPD



The performance of the product is in conformity with the declared performance range.

This declaration of performance is issued in accordance to Regulation (EU) 305/2011 as it has effect in the United Kingdom under sole responsibility of the manufacturer listed above.

Signed for and on behalf of the manufacturer by Paweł Lisiński in Piotrków Tryb., on 15.05.2023

WIM Sp. z o.o.
Wiceprezes Zarządu
Paweł Lisiński
Paweł Lisiński