

Unique identification code of the product-type:	WIM WYLEWKA MAX 30 (2023)
Intended use or uses:	EN 13813 CT-C30-F7 Cement-based subfloor, for use inside the buildings.
Manufacturer:	WIM Sp. z o.o. ul. 18 Stycznia 28 97-300 Piotrków Trybunalski www.wim-chb.pl
System or systems of assessment and verification of constancy of performance:	System 4
Designated standard:	EN 13813:2002

Declared performance:

Essential characteristics	Performance
Reaction to fire (in case of exposure).	A1 _{fl}
Corrosive substance release.	CT
Strength: <ul style="list-style-type: none"> Compressive strength Flexural strength. 	C30 F7
Durability of initial tensile adhesion against climate / heat ageing action: <ul style="list-style-type: none"> tensile adhesion strength after heat ageing 	≥ 0,5 N/mm ²
Durability of initial tensile adhesion against water / humidity action: <ul style="list-style-type: none"> tensile adhesion after water contact 	≥ 0,5 N/mm
Durability of initial tensile adhesion against contact with lime water: <ul style="list-style-type: none"> tensile adhesion after contact with lime water 	≥ 0,5 N/mm ²
Durability of initial tensile adhesion after against freeze-thaw cycles: <ul style="list-style-type: none"> tensile adhesion after freeze-thaw cycles 	≥ 0,5 N/mm ²
Release of dangerous substances	NPD



The performance of the product is in conformity with the declared performance range.

This declaration of performance is issued in accordance to Regulation (EU) 305/2011 as it has effect in the United Kingdom under sole responsibility of the manufacturer listed above.

Signed for and on behalf of the manufacturer by Paweł Lisiński in Piotrków Tryb., on 21.08.2023

WIM Sp. z o.o.
Wiceprezes Zarządu
Paweł Lisiński
Paweł Lisiński